


Alu Zinc Decorative Sandwich Panel PU Customized

Our Product Introduction


Basic Information

- Place of Origin: HEBEI, CHINA
- Brand Name: BAODU
- Minimum Order Quantity: 500square meters
- Price: \$6-7square meter
- Packaging Details: In general, for steel structure , we use the steel frame packing to keep goods not to be broken . For sandwich panel and color steel sheet, we use the plastic packing . If the clients need special packing will according to their requirements.
- Delivery Time: 15days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 10000 Perch/Perches per Month stainless steel perforated metal sheet



Product Specification

- Width: 380 Mm
- Use: Roof, Wall
- Color: Customized
- Product Name: 16mm Decorative PU Foam Sandwich Panel Insulated Metal Carved Exterior Wall Panel
- Application: External Interior Wall Panel Insulation
- Thickness: 16mm
- Project Solution Capability: Graphic Design, 3D Model Design,
- Length: Customized
- Warranty: More Than 5 Years
- After-sales Service Provided: Online Support, Video Technical Support
- Highlight: **Alu Zinc Decorative Sandwich Panel, Customized Decorative Sandwich Panel, Customized sandwich panel pu**



for more products please visit us on baodupanel.com

Product Description

Baodu panel is made up of three layers: the top material is embossed metal board coated with Alu-zinc, the middle is fire- safe material and polyurethane foaming and the back is glass fibre paper.

Three layers	Material	Thickness
Top layer	Embossed metal board coated with Alu-zinc	0.3mm
Middle layer	Polyurethane foaming with fire-safe material	15.5mm
Back layer	Glass fibre paper.	0.2mm

The length of Baodu Panel is 3000mm-6000mm, standard length is 3800mm, width is 380mm, and thickness is 16mm.

Length	Width	Thickness
3000-6000mm (standard length: 3800mm)	380mm	16mm


Structure




side elevation





front plan



sectional drawing






Technical Index of B1 and B2			
1	Fire-resistance Grade	B1	B2
2	Core Material	PIR	PUR
3	Weight (3 layers)	4.1kg/m ²	3.6kg/m ²
4	Density(core material)	45kg/m ³	31.2kg/m ³
5	Thermal Conductivity	0.018w/mk	0.024w/mk
6	Thermal Resistance	1.8m ² ·k/w	0.73m ² ·k/w
7	Heat Transfer Coefficient	0.51w/(m ² ·k)	1.14w/(m ² ·k)
8	Water Absorption Rate	0.90%	2.50%
Tips 1: PIR is mainly for government project, chemical plant, cold storage etc.			
2: PUR is mainly for common residential buildings.			

Accessory System

Baodu accessory is made up of 6 parts: starting, finishing, connection, out corner, in corner and window part. There are 2 kinds of accessory :aluminum and metal board.



Packing & Delivery



Project Case





+86 13717927965



chunlei.song@baodu.com



baodupanel.com

Room 1101, Building 6, Yard 9, Hongye Road, Daxing District, Beijing